SECTION 1: IDENTIFICATION					
Trade Name & Synonyms	Sulfur, Pulverized Sulfur, Feed Grade Sulfur, Commercial Sulfur				
Chemical Name	Sulfur				
CAS Number	7704-34-9				
Family Name	Element – Sulfur				
Chemical Formula	S ₈				
Recommended Use	Animal feed, various industrial applications				
Restrictions on Use	Keep away from heat sources, sparks, or open flames				
Manufacturer/Supplier	Sales and Technical ServicesShipping and ReceivingInternational Sulphur, Inc.International Sulphur, Inc.P. O. Box 6111386 North Frontage RoadMt. Pleasant, TX 75456Mt. Pleasant, Texas 75455Tel: (903) 577-5500Tel: (903) 577-5500Fax: (903) 577-5540Fax: (903) 577-5540isulphur@internationalsulphur.comGPS Coordinates: 33° 9' 34" N 95° 03' 29" W				
Emergency Assistance	CHEMTREC Tel: (800) 424-9300 within the USA Tel: 001-703-527-3887 outside the USA				

SECTION 2: HAZARDS IDENTIFICATION

GHS Information:

Classification: Skin irritant, Category 2

OSHA Defined Hazards: Combustible Dust

GHS Label Elements

Pictogram(s):



Signal Word: Warning

Hazard Statement: May cause skin irritation. May form combustible dust concentrations in air.

Hazard Statement	H303: May be harmful if swallowed.	
	H316: May cause mild skin irritation.	
	H320: May cause eye irritation.	
	H335: May cause respiratory irritation.	
Prevention Statement	P210: Keep away from heat/sparks/open flames/hot surfaces. No smoking.	
	P220: Keep away from oxidizing agents.	
	P242: Use non-sparking tools when available.	
	P243: Take precautionary measures against static discharge.	
	P261: Avoid breathing dust/fume/gas/mist/vapors/spray.	
	P264: Wash hands thoroughly after handling and before eating.	
	P284: In case of inadequate ventilation, wear respiratory protection.	
Response Statement	P362: Take off contaminated clothing.	
	P363: Wash contaminated clothing before reuse.	
	P370+P378: In case of a fire, use water fog, spray, or regular foam to	
	extinguish. Do not use a direct water stream.	
	P381: Eliminate all ignition sources.	
Storage Statement	P402: Store in a dry place.	
	P403: Store in a well-ventilated place.	
	P404: Store in a closed container.	

SECTION 2: HAZARDS IDENTIFICATION

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Characterization

Mixture

Product	Percentage Contained	CAS Number
Sulfur	>99.85%	7704-34-9

Hazardous Ingredient None

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures	
Skin	Wash skin thoroughly with mild soap and water. Wash exposed clothing separately
	before reuse.
Еуе	Immediately flush eyes with plenty of water for 15 minutes, while holding upper and
	lower lid apart to insure rinsing of entire eye surface and lids. Do not use boric acid to
	rinse with. FOR SEVERE IRRITATION, SEEK MEDICAL ATTENTION, preferably an
	ophthalmologist
Inhalation	Move victim to fresh air. Watch for signs of an allergic reaction. Use a bronchodilator
	inhaler if directed by asthma patient. Keep victim warm and quiet. If not breathing, give
	artificial respiration. If heart has stopped beating, start cardiopulmonary resuscitation
	(CPR). SEEK MEDICAL ATTENTION.
Ingestion	Give one tablespoon of Syrup of Ipecac to induce vomiting. If vomiting does occur, give
	fluids again. If vomiting has not occurred in twenty minutes, the same dose of Syrup of
	Ipecac may be repeated one additional time. Alternatively, vomiting may be induced by
	touching the back of the throat with a finger. Do not give anything by mouth to an
	unconscious or convulsing person. SEEK MEDICAL ATTENTION.

SECTION 4: FIRST AID MEASURES (CONT)

Most Important Symptoms and Effects (Long-Term and Acute)

Refer to Section 11: Toxicological Information

Indication of any Immediate Medical Attention or Special Treatment Needs

Individuals with known allergies to sulfide drugs may also have allergic reactions to elemental sulfur

SECTION 5: FIREFIGHTING MEASURES				
Suitable Extinguishing Media	Water fog, spray, or regular foam. Do not use a direct water stream.			
Unsuitable Extinguishing Media	Do not use solid streams of water, which could create sulfur dust clouds and cause an explosion or could move burning sulfur to adjacent areas.			
Exposure Hazards	Prevent human exposure to smoke, fumes, or products of combustion (sulfur oxi gases). Evacuate nonessential personnel from the fire area. If large fire, evacuate peop downwind from fire. Consider evacuation for ½ mile in all directions.			
Advice for Firefighters	Firemen exposed to contaminated smoke should be immediately relieved and checked for symptoms of exposure of toxic gases. This should not be mistaken for heat exhaustion or smoke inhalation. <u>Seek medical attention immediately!</u>			
Protective Equipment	Wear full-faced, self-contained breathing apparatus and full protective clothing.			
Fire and Explosion Hazards	Fire will rekindle until mass is cooled below 310°F (154°C). Cool surrounding areas with water fog to prevent re-igniting. Sulfur dust is HIGHLY FLAMMABLE. If suspended in air, it will ignite by friction, static electricity, heat, sparks, or flames. Sulfur dust clouds may explode.			
Combustion Products	Sulfur oxide gases			

	SECTION 6: ACCIDENTAL RELEASE MEASURES
Personal Precautions	Minor spills such as torn or ruptured containers should be repaired or patched with tape if possible. Place spilled material in a disposable container. Avoid getting dust in eyes.
Protective Equipment	Maintain adequate ventilation. Wear a dust mask when dust is present or a respirator if smoke is present. Wear safety glasses.
Emergency Procedures	As an immediate precautionary measure isolate spills or leak areas. Eliminate all sources of ignition, such as flares, sparks, or flames, in the immediate area. No smoking. Ventilate closed spaces before entering.
Environmental Precautions	Do not allow runoff to enter lakes or waterways.
Containment/Cleanup Measures	Gently sweep or shovel up spilled material using a natural fiber broom and/or aluminum shovel to prevent sparking, to avoid creating a dust cloud. Place sweepings in an appropriate chemical waste container for reclaiming or disposal in an approved facility. Wash spill site after clean-up is complete.

SECTION 7: STORAGE AND HANDLING				
n g ig re	All handling and conveying equipment should be properly grounded and bonded. Be careful not to create dust. Avoid any conditions that might tend to create a dust explosion. Maintain good housekeeping practices to minimize dust build-up and dispersion. Eliminate sources of ignition. Keep away from heat, sparks, and flames. Use nonferrous tools, when available, to reduce sparking. Gently sweep or shovel up spilled materials using a natural fiber broom and/or aluminum shovel to prevent sparking. Maintain adequate ventilation in all areas.			
Conditions for Safe Storage, Includin	g any Incompatibilities:			
C St ch	ontainers should be stored in a cool, dry, well-ventilated area. Keep container tightly closed. tore away from flammable materials, sources of heat, flames, and sparks. Separate from hlorates, nitrates, and other oxidizing agents. Exercise due caution to prevent damage to or eakage from container.			
-	eep away from flammable materials, sources of heat, flame, sparks, chlorates, nitrates and her oxidizing agents.			
SECTION	8: EXPOSURE CONTROLS/ PERSONAL PROTECTION			
Engineering Measures/Controls	Maintain adequate ventilation in all areas. No flares or flames in area. Be careful not to create dust. Eliminate sources of ignition.			
Personal Protective Equipment				
Pictograms				
Respiratory	Wear dust masks and use NIOSH/MSHA approved dust respirator if airborne concentrations exceed exposure limits.			
Eyes/Face	Wear suitable, protective safety glasses to prevent eye irritation from dust.			
Hands	Wash hands thoroughly after handling and before eating or smoking.			
Skin/Body	Wear suitable, protective clothing to prevent skin irritation from dust. Wash skin thoroughly after handling and before eating or smoking. Wash contaminated clothing separately before reuse.			
Environmental Exposure Controls	Follow best practice for site management and disposal of waste. Avoid release to the environment.			
General Industrial Hygiene Considera	ations Protective equipment should be used in any situation that may result in hazardous exposure. Maintain good housekeeping practices to minimize dust build-up and dispersion. Eliminate sources of ignition. Use nonferrous tools to reduce sparking. Sweep or shovel up spilled material using a natural fiber broom and/or aluminum shovel to prevent sparking. Maintain adequate ventilation in all areas.			

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Solid		
Appearance	Yellow colored lumps, crystals, powder, or formed shape		
Formula	S ₈ (Rhombic or monoclinic)		
Odor	Odorless, or faint odor of rotten eggs		
Odor Threshold	No data available		
рН	No data available		
Boiling Point	832° F (444° C)		
Melting/Freezing Point	118-120°C (244-248°F)		
Flash Point	207°C (405°F) Closed Cup		
Evaporation Rate	No data available		
Flammability	Sulfur dust may form combustible concentrations		
Flammable/Explosion Limits	Upper: 6.38% (v) Lower: 0.17% (v)		
Vapor Pressure	8mmHg at 246°C (475°F) 1mmHg at 183.8°C (362.8°F)		
Vapor Density	No data available		
Purity	99.5% Min.		
Auto-Ignition Temperature	240°C (464°F)		
Decomposition Temperature	Does not decompose		
Viscosity	Not applicable		
Specific Gravity	2.07 @ 70° F		
Solubility in Water	Insoluble		
Bulk Density	Lumps: 75-115 lbs. /ft ³ Powder: 33-80 lbs. /ft ³		

SECTION 10: STABILITY AND REACTIVITY

Chemical Stability	Stable
Conditions to Avoid	Keep from heat sources, sparks, and open flames
Incompatible Materials	Oxidizing agents, copper, copper alloys, steel, chlorates, nitrates
Possibility of Hazardous Reactior	ns Oxidizing agents may react violently
Hazardous Decomposition	Oxides of sulfur gases produced by burning sulfur
Products	
Hazardous Polymerization	Will not occur

SECTION 11: TOXICOLOGICAL INFORMATION				
Likely Routes of Exposure	Inhalation, ingestion, skin contact, and eye contact			
Signs and Symptoms of Overexposure	Nose or throat irritation, coughing, chest discomfort, asthma, difficulty breathing, nausea, vomiting, stinging eye irritation, skin irritation, hives.			
Exposure Limits	No exposure limits have been established			
Acute Symptoms and Effects Inhalation	Prolonged inhalation may cause irritation of respiratory tract. Breathing of dust may aggravate asthma and other pulmonary diseases.			
Eye Contact	Sulfur dust is an eye irritant.			
Skin Contact	No adverse effects; however, skin irritation may be aggravated in persons with existing skin lesions.			
Ingestion	Ingested sulfur is converted to sulfides in the gastrointestinal tract, and ingestion of 10 to 20 grams has caused irritation of the GI tract and renal injury. Swallowing large amounts may cause nausea and vomiting.			

		SECTION 11:	TOXICOLOGICAL IN	IFORMATION (CON	IT)	
Long-Te	erm Effects	None knowr	n to humans			
Toxicity LD ₅₀ LC ₅₀ Skin Eye		Oral: >5050 mg/kg (rats) Dermal: >2020 mg/kg (rats) Inhalation @ 90%: >5.49-mg/L air concentration (rats) Slightly irritating (rabbits) Minimal irritation in non-washed eyes (rabbits)				
	56	ensitization	Reproductive Effects	Developmental Effects	Endocrine Disruptor	
		t Established	Not Established	Not Established	Not Established	
	<u>(</u>	<u>Carcinogenicity</u>	<u>Terat</u>	ogenicity	Mutagenicity	
	This product of	does not contain any ing	redient designated by NTP	, IARC, or OSHA as a proba	ble human carcinogen.	
		SECTIO	N 12: ECOLOGICAL	INFORMATION		
Toxicity And Ot	xicity xicity to fish LC50- Oncorhynchus mykiss (rainbow trout) -> 180 mg/l -96h LC50- other fish- 866 mg/l -96h xicity to Daphnia EC50- Daphnia magna (Water flea) -> 5,000 mg/l -48h vertebrates					
Results	ÿ	No data available No data available No data available No data available PBT/vPvB assessmen	t not available as chemical	safety assessment not req	uired/not conducted	
		SECTIO	N 13. DISPOSAL CO	NSIDERATIONS		
Waste	Treatment Meth	nods				_
Produc	duct Waste Dispose of content and/or container in accordance with local, regional, national, and/or international					

Packaging Waste Dispose of content and/or container in accordance with local, regional, national and/or international regulations.

SECTION 14: TRANSPORTATION INFORMATION

Solid sulfur is not regulated if transported in non-bulk packaging (less than 400kg per package) or if formed to a specific shape, such as prills, granules, pellets, pastilles, or flakes (49 CFR 172.102, special provision 30).

US and Canadian Shipments

Bulk containers (packaging) of powdered sulfur of more than 400 kg (880 lbs.) per package

regulations.

	14.1 UN	14.2 UN proper	14.3 transport hazard	14.4 packaging	14.5 environmental
	number	shipping name	class(es)	group	hazards
DOT	NA1350	Sulfur (Sulphur)	9 (Misc. Hazardous	III	No data available
(Domestic)			Materials)		
DOT	UN1350	Sulphur (Sulfur)	4	III	No data available
(International)					
TDG	UN 1350	Sulfur	4.1	III	No data available

SECTION 14: TRANSPORTATION INFORMATION (CONT)

Other than US and Canadian Shipments

All shipments of powdered sulfur

IMO/IMDG	UN1350	Sulphur (Sulfur)	4.1 (flammable solid)	III	No data available
IATA/ICAO	UN1350	Sulfur	4.1	III	No data available

This product is not a Marine Pollutant as defined in 40 CFR Part 172.

Pictograms for Hazard Classes	Powdered sulfur packaging over 400 kg (880 lbs.) only					
Special Precautions for User	None specified					
SECTION 15: REGULATORY INFORMATION						
TSCA	This product is listed on the TSCA Inventory at CAS Registry Number 7704-34-9.					
CERCLA	 Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) If this product is accidentally spilled, it is not subject to any special reporting. We recommend that you contact state and local authorities to determine if there are other local reporting requirements. 					
SARA TITLE III	Superfund Amendments and Reauthorization Act, Title III Sections 311/312: None. Section 313: None. Section 302: None. 					
RCRA	Resource Conservation and Recovery Act					
	Not subject to reporting because sulfur is not identified as a hazardous waste.					
SECTION 16: OTHER INFORMATION						
Last Revision Date	03/28/2019 Preparation Date 05/01/2015					
Additional Information	For additional information, contact your technical sales representative. For additional health and safety information, call Georgia Gulf Sulfur Corporation at 229-244-0000.					
Disclaimer/						
Statement of Liability	THE INFORMATION CONTAINED HEREIN IS BASED ON THE PRESENT KNOWLEDGE AND DATA AVAILABLE TO US AND IS BELIEVED TO BE CORRECT. HOWEVER, INTERNATIONAL SULPHUR. INC. MAKES NO WARRANTY, EXPRESSED OR IMPLIED, REGARDING THE ACCURACY OF THIS DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. FURTHERMORE, THIS SHALL NOT CONSITUTE A GUARANTEE FOR ANY SPECIFIC PRODUCT FEATURES AND SHALL NOT ESTABLISH AND LEGALLY VALIDIFY A CONTRACTUAL RELATIONSHIP. INTERNATIONAL SULPHUR, INC. ASSUMES NO RESPONSIBILITY FOR INJURY FROM THE USE OF THE PRODUCT DESCRIBED HEREIN.					