

L.V. Lomas Ltd  
99 Summerlea Rd  
Brampton; Ontario; L6T 4V2  
Canada



PRODUCT: Sulphur H10

CODE: Z ALD010A



### Section 01: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURER..... HOLLY INDUSTRIES  
P.O. BOX 149  
ACTON  
ON  
CDN  
L7J 2M3  
PRODUCT NAME..... Sulphur H10  
OFFICE NUMBER..... 519-853-0120.  
AFTER HOURS NUMBER..... 519-763-0786.  
PACKAGING SIZE..... Super sacks.  
PRODUCT CODE(S)..... Z ALD010A  
MATERIAL USE..... Agriculture. Pulp & paper. Cement. Adhesive.  
PRODUCT USE..... Industrial.  
CHEMICAL FAMILY..... Sulphur.  
SYNONYMS..... Rubbermakers Sulphur H10.  
24 HOUR EMERGENCY NUMBER:..... CALL Newalta Industrial Services 1-800-567-7455.

### Section 02: COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredients	%	Exposure Limit	C.A.S.#	LD/50, Route, Species	LC/50 Route, Species
Sulphur	97.0	Not Indicated	7704-34-9	Oral Rat > 5,050 mg/kg Dermal Rat > 2,020 mg/kg	Inhalation @ 90% Rat > 5.49 mg/L

### Section 03: HAZARDS IDENTIFICATION

SIGNAL PHRASE..... Flammable Solid.  
ROUTE OF ENTRY ..... Eye contact. Skin contact. Inhalation. Ingestion.  
SKIN CONTACT..... May cause skin irritation. Avoid skin contact.  
EYE CONTACT..... May cause eye irritation. Avoid eye contact.  
INGESTION..... Do not ingest.  
INHALATION..... May cause irritation of nose, throat or respiratory tract. Avoid inhalation.  
MEDICAL CONDITIONS AFFECTED BY .... None known.  
EXPOSURE  
SIGNS OF OVER EXPOSURE..... No additional remark.

### Section 04: FIRST AID MEASURES

SKIN CONTACT..... Wash affected area immediately with large amounts of soap and water. If irritation develops or persists, seek medical attention.  
EYE CONTACT..... Immediately hold eyelids open and flush with water for at least 15 minutes. If irritation develops or persists, seek medical attention.  
INHALATION..... If affected, move to fresh air. If breathing has stopped, perform artificial respiration. Seek immediate medical attention.  
INGESTION..... DO NOT induce vomiting. Give victim two glasses of water. Seek immediate medical attention.  
NOTES TO PHYSICIAN..... Watch for delayed metabolic acidosis if ingested in large quantities. Treat symptomatically.

### Section 05: FIRE FIGHTING MEASURES

FLASH POINT (°C), METHOD..... 207.2 C.  
AUTO IGNITION TEMPERATURE (°C)..... 248 - 266 C.  
LOWER FLAMMABLE LIMIT (% VOL)..... 35 g/m3.  
UPPER FLAMMABLE LIMIT (% VOL)..... 1,400 g/m3.  
FLAMMABILITY..... Com I.  
HAZARDOUS COMBUSTION PRODUCTS.. Sulphur dioxide and trioxide.  
UNUSUAL FIRE / EXPLOSION HAZARDS.. Dust-air mixtures have potential to explode. Fire will rekindle until cooled below 154 C. Assure all equipment is properly grounded to prevent static discharges, and vented to provide for potential energy release. Avoid heat, sparks and open flames.  
SENSITIVITY TO MECHANICAL IMPACT.... Not sensitive.  
SENSITIVITY TO STATIC DISCHARGE..... Dust suspended in air in critical proportions and in the presence of an ignition source may cause explosion.

PRODUCT: Sulphur H10

CODE: Z ALD010A

**Section 05: FIRE FIGHTING MEASURES**

EXTINGUISHING MEDIA..... Water spray, foam, dry powder or carbon dioxide.  
 SPECIAL FIRE FIGHTING PROCEDURES.. Avoid hose streams or any method which will create dust clouds. Evacuate all persons to a safe area. Use water spray to cool containers. Firefighters should wear protective equipment as required.

**Section 06: ACCIDENTAL RELEASE MEASURES**

LEAKS AND SPILLS..... Avoid creating dust. Use appropriate tools to put the spilled material in a convenient waste disposal container. Eliminate sources of ignition. Do not allow product to enter sewers or waterways. Use non-sparking tools. Wear protective clothing during cleanup.

**Section 07: HANDLING AND STORAGE**

HANDLING PROCEDURES..... Avoid creation of respirable dust. Avoid contact with eyes and skin. Avoid inhalation and ingestion. If airborne dust is generated, eliminate all sources of ignition that may come into contact with the dust. Use under well ventilated conditions. Wash skin thoroughly after handling and before eating or smoking. Wash with soap and water. Use good industrial hygiene practices in handling this material.  
 STORAGE NEEDS..... Do not store in open, unlabeled or mislabeled containers. Keep container tightly closed. . Post "NO SMOKING OR OPEN FLAMES" sign. Store in a cool, dry, well-ventilated area.

**Section 08: EXPOSURE CONTROLS / PERSONAL PROTECTION**

VENTILATION REQUIREMENTS..... Local ventilation may be required during certain operations to maintain concentrations below recommended exposure limits.  
 PROTECTIVE EQUIPMENT  
 EYE/TYPE..... Safety glasses with sideshields, faceshield, and/or goggles to protect against airborne dust.  
 GLOVES/ TYPE..... Wear protective gloves.  
 RESPIRATORY/TYPE..... A NIOSH/OSHA approved dust respirator should be worn. Determine the appropriate type by consulting the respirator manufacturer.  
 CLOTHING/TYPE..... Wear impervious clothing and boots to prevent skin contact.  
 FOOTWEAR/TYPE..... No special footwear is required.  
 BODY/TYPE..... No special protective clothing is required.

**Section 09: PHYSICAL AND CHEMICAL PROPERTIES**

PHYSICAL STATE..... Yellow flakes, prills, granules, pellets or pastilles.  
 ODOUR..... Faint odour of rotten eggs.  
 ODOUR THRESHOLD (ppm)..... Not available.  
 VAPOUR DENSITY (AIR=1)..... Not available.  
 BULK DENSITY..... Lumps 75 - 115 lbs/ft<sup>3</sup> ; Powder 33 - 80 lbs/ft<sup>3</sup>.  
 % VOLATILE..... Not available.  
 VAPOUR PRESSURE (mm Hg)..... 0 mmHg @ 137.8 C.  
 EVAPORATION RATE..... Not applicable.  
 BOILING POINT (°C)..... 444 C.  
 pH..... Not available.  
 SOLUBILITY IN WATER (% W/W)..... Insoluble.  
 SPECIFIC GRAVITY..... 2.07 @ 21.1 C.  
 COEFFICIENT OF WATER/OIL ..... Not applicable.  
 DISTRIBUTION  
 FREEZING POINT ( °C)..... 110 - 119 C.  
 MELTING POINT (°C)..... 110 - 119 C.

**Section 10: STABILITY AND REACTIVITY**

HAZARDOUS POLYMERIZATION..... Will not occur.  
 STABILITY..... Stable.  
 INCOMPATIBILITY..... Strong oxidizing agents. Corrosive to copper & copper alloys. Damp sulfur will corrode steel.  
 CONDITIONS TO AVOID..... Ignition sources. Keep away from excessive heat or open flame.  
 HAZARDOUS PRODUCTS OF DECOMPOSITION ..... Sulphur oxides.

**Section 11: TOXICOLOGICAL INFORMATION**

TOXICITY EFFECTS ON ANIMALS..... Not available.  
 TOXIC EFFECTS ON HUMANS..... Irritant in case of eye contact. Irritating to skin.  
 CHRONIC EFFECTS ON HUMANS..... No specific information is available in our database regarding the other chronic toxic effects of this material for humans.  
 CARCINOGENICITY..... No evidence of carcinogenic effects according to ACGIH or IARC.  
 TERATOGENICITY..... No evidence of teratogen effects.  
 MUTAGENICITY..... No evidence of mutagenic effects.

PRODUCT: Sulphur H10

CODE: Z ALD010A

**Section 11: TOXICOLOGICAL INFORMATION**

REPRODUCTIVE EFFECTS..... No evidence of reproductive effects.

**Section 12: ECOLOGICAL INFORMATION**

ECOTOXICITY DATA..... Not available.

PRODUCTS OF DEGRADATION..... No specific information is available in our database regarding the degradation of this product.

BIODEGRADABILITY..... Not determined.

**Section 13: DISPOSAL CONSIDERATIONS**

WASTE DISPOSAL..... Dispose in a suitable waste treatment facility in compliance with all federal, provincial and local regulations.

**Section 14: TRANSPORT INFORMATION**

SHIPPING NAME..... Sulfur.

UN NUMBER..... UN1350.

CLASS..... Class 4.1.

PACKAGING GROUP..... PGIII.

**Section 15: REGULATORY INFORMATION**

CEPA STATUS..... All the ingredients are on the DSL list.

WHMIS CLASSIFICATION..... WHMIS Class B4: Flammable Solids.

**Section 16: OTHER INFORMATION**

REFERENCES..... Manufacturer's Material Safety Data Sheet.

TELEPHONE NUMBER:..... 905-458-7111.

PREPARED BY: ..... Regulatory Affairs

PREPARATION DATE: ..... Jul23/12

DISCLAIMER:..... L.V. Lomas Limited ("Lomas") expressly disclaims all express or implied warranties of merchantability and fitness for a particular purpose, with respect to the product or information provided herein, and shall under no circumstances be liable for incidental or consequential damages. All information appearing herein is based upon data obtained from the supplier. While the information is believed to be accurate, Lomas makes no representations as to its accuracy or sufficiency. Conditions of use are beyond Lomas' control and therefore users are responsible to verify this data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of the product, or from the publication or use of, or reliance upon, information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process